

SPECIFICATION FOR STYLE NO. 9049



1. GENERAL

- 1.1 Tan lined apollo leather rigger boot with steel toe cap and steel midsole with Scuff cap to EN ISO 20345 – S1P SRC
- 1.2 Dual density polyurethane anti static sole with Scuff cap
- 1.3 Constructed to comply with the requirements of EN ISO 20345:2011

2. DETAIL

2.1 Upper

Light tan print full apollo leather, blocked vamp. Pull-on loops with ankle support.

2.2 Vamp Lining

Rot proof synthetic EN ISO 20344.

2.3 Quarter Lining

Padded collar Beige fur fabric to EN ISO 20344.

2.4 Insole

Fur lined footbed to EN ISO 20344.



2.5 Steel Toe Cap

200 Joules, to EN ISO 20345

2.6 Sole and Heel

Injected dual density polyurethane (ICI) To EN ISO 20344. Oil, acid, alkali resistant sole .

2.7 Penetration Resistant Midsole

Penetration resistant stainless steel to EN ISO 20345.

3. PERFORMANCE REQUIREMENTS

3.1 Impact Resistance

When the boot is subjected to the 200 Joules impact test as specified in EN ISO 20345, the minimum clearance inside the steel cap area shall not be less than the appropriate value given in Table 6 of EN ISO 20345. (14mm for size 8).

3.2 Compression Resistance

When the footwear is tested in accordance with EN ISO 20345, the minimum clearance inside the steel cap area shall not be less than the appropriate value given in Table 6 of EN ISO 20345 (14mm for size 8 when subjected to 15,000 N.)

3.3 Penetration Resistant Midsole

When footwear is tested in accordance with the method described in clause 6.2 of EN ISO 20345, the force required to penetrate the sole unit shall not be less than 1100N.

---end---

